

High resolution, full frame CMOS sensor delivering incredible detail. The ultimate Digital SLR for Professional Photographers.

EOS-1Ds
Mark III DIGITAL

A Canon developed 21.1 Megapixel Full-frame CMOS Sensor and Dual DiGiC III image processors combine to deliver ultra fine image detail. With the ability to capture up to 5fps at 21.1 Megapixels with a continuous burst of up to 56 shots (JPEG) the EOS-1Ds Mark III is the premier DSLR on the market. Key new features include the EOS Integrated Cleaning System and two Live View Modes that can be used to shoot while viewing images in real time. Comprised of a strong and durable magnesium alloy body with over 70 waterproof and dust proof seals, the EOS-1Ds Mark III is the ultimate DSLR for Professionals.



Key Features

Outstanding Image Quality

- 21.1 Megapixel CMOS Sensor
- Dual DiGiC III Image Processor
- 14-bit A/D colour conversion
- Picture Style

High Performance Operation

- 5 fps (up to 56 in a single burst)
- 45-point AF system
- 1/8000 sec – 30 sec
- Selectable ISO 100-1600 (expansion to 50 and 3200 with Custom Functions)

Professional Features

- Magnesium Alloy Body with over 70 dust and moisture resistant seals
- Viewfinder with 100% coverage & zoom magnification of 0.76x
- 57 Custom Functions
- Two Live View Modes
- EOS Integrated Cleaning System
- Huge 3.0" fine detail LCD Screen

Incredible Image Detail

21.1 Megapixel Full Frame CMOS Sensor captures even the finest details

Superior Image Processing

Dual DiGiC III Image Processors produce ultra fine detail and 14-bit A/D for fine colour gradation

Choose a new look

The new Picture Style button makes it even easier to customise images on camera

Fast Operation

Capture an amazing 5 fps with the ability to capture up to 45 shots in a single continuous burst

Blemish Free Images

EOS Integrated Cleaning System provides total protection from appearance of sensor dust in images

Sharpest Focus

45-point AF system (including 19 cross-type AF points & 26 assist AF points)

Live View Mode

Shoot on-camera or wirelessly via a computer in real time with Live View

See more detail

Huge 3.0" fine detail LCD Screen to view extreme detail



20 Years of Innovation

The first fully electronic lens. The first image stabilising lens. The first full-frame digital SLR. The first to shoot 10 frames per second. Driven by Canon's imaging heritage EOS has been redefining SLR photography since 1987. And we don't intend to stop.

EOS-1Ds Mark III Technical Specifications

Imaging	
Imaging Sensor/Effective Pixels	CMOS / 21.1 megapixels
Effective Sensor Size	36 x 24 mm
A/D Resolution Power	14-bit
Colour Filter Size	RGB Primary Colors
35mm Focal Length Equivalent	1.0x
Image Recording	
Medium	CF Type I, II / SD (incl SDHC), external media (via WFT-E2)
Image Size	
Large / Fine	6.4 MB (5616 x 3744 pixels)
Middle / Fine	5.2 MB (4992 x 3328 pixels)
Middle / Normal	3.9 MB (4080 x 2720 pixels)
Small / Fine	2.2 MB (2784 x 1856 pixels)
RAW	25.0 MB (5616 x 3744 pixels)
sRAW	14.5 MB (2784 x 1856 pixels)
RAW & JPEG Simultaneous Recording	Yes
Viewfinder	
Coverage (vertical/horizontal)	1.00
Dioptric Adjustment	-3 to +1 dpt
Interchangeable Focusing Screens	Yes
Autofocus	
AF Points	19 cross type + 26 assist
Exposure Control	
Shooting Modes	5
Metering Segments	63
Metering Modes	Evaluative, Partial, Spot (Centre-spot, AF point spot, multi spot), Centre-weighted
ISO Speed Range	ISO 100-1600 (expandable to 50-3200 via CF)
Exposure Compensation	Manual, AEB - 1/3 or 1/2-stop increments, ±2
Shutter	
Shutter Speed	1/8000 sec - 30 sec, X-sync at 1/250 sec
Flash Control	
E-TTL II Autoflash	Yes (with EX-series Speedlite)
Built-in Flash / G. No.	No
Speed	
Shooting Speed	5 fps / 56 shot max burst
White Balance	
Settings	6 standard + 5 custom
WB Bracketing	Yes
General Features	
LCD Monitor	TFT - 3.0 inch
Custom Functions/Settings	57
Personal Functions/Settings	Yes
Integrated Cleaning System	Yes
Live View	Yes
External Interface	USB 2.0 / Video / PC Terminal / Extension System
Remote Control/Type	USB 2.0 / N3 Remote Control / extension System
Battery	Lithium Ion
Chassis Material	Magnesium Alloy + Stainless Steel
Water/Dust Resistance	Yes (water resistance retained with 580EXII)
Dimensions (W x D x H) mm	156 x 79.9 x 159.6 mm
Weight (excl. battery in grams)	1,210

Subject to change without notice



Standard Accessories

- Battery Pack LP-E4
- Battery Charger LC-E4
- AC Adapter Kit ACK-E4
- Video Cable VC-100
- Interface Cable IFC-200U
- Eyecup Eg
- Wide Strap L6
- USB Cable Protector
- CR2025 Lithium Battery
- Interface Cable IFC-500U

Software Included

- EOS DIGIATL Solution Disk
- Software Instruction Manual

Optional Accessories

- Over 60 EF Lenses
- Macro Ring Lite MR-14EX
- Dioptric Adjustment Lenses Eg:
 - Angle Finder C
 - Hand Strap E1
- Canon EX-series Speedlites
- Macro Twin Lite MT-24EX
- Anti-Fog Eyepiece Eg:
 - Range of Focusing Screens



Wireless File Transmitter

- WFT-E2



Timer Remote Controller

- TC-80N3



Remote Switch

- RS-80N3



Wireless Control

- LC-5



Original Data Security Kit

- OSK-E3



Car Battery Cable

- CB 570